



Acoustic absorption value $\alpha_w$	0,90
acoustic absorption class	A

Type of assembly E-50 according to DIN EN ISO 354 - lying on the ground  
DESCOR<sup>®</sup> PREMIUM acoustic in front of 40 mm airspace  
absorbed with 40 mm ISOVER SSP2

WEISS/ WHITE  
00900 - 085

SCHWARZ/ BLACK  
00347 - 086



REF.

**DESCOR® PREMIUM acoustic**

Colour number  
699144 - ##### - ###



polyester knitted fabric with polyurethane coating (PU)  
with micro-perforation (invisible)  
air permeable



**B1** **DIN EN**  
13501-1  
B-s1, d0



185 g/m<sup>2</sup> ± 5%



ca. 380 μm ± 10



50m/55yrd



15 x superior to PVC films

Specs



$\alpha_w$

DIN EN ISO 354 - test report no 086-12-G01 (Akustikbüro Krämer + Stegmeier)



Gross in cm (inch)	320 (126)	420 (165)	520 (205)
Net in cm (inch)	310 (122)	410 (161)	505 (199)

DESCOR® PREMIUM solely applies to building professionals.  
The system is exclusively used by specialists trained in this technique.  
A list of recommended approved fitters is available on request.